

ST. PAUL DISTRICT RECOMMENDED BEND WIDTHS

April 1996

Reproduced From Attachment 3 of the GREAT I Technical Appendix E, Volume 3, September 1980

Bend Location	River Mile	Normal Width Before Dredging	Normal Width After Dredging	Width at Last Sounding	Maximum Potential Width	Suggested Width
Below Lock and Dam 1	846.3-846.7			150	200	150
Fort Snelling	845.7-846.3			200	250	200
Lower Mouth - Minnesota River	843.3-844.3			250	300	300
Lilydale, Minnesota	841.7-842.4			300	350	300
Below Omaha Railroad Bridge	840.7-841.4			250	250	250
Above Beltline Railroad Bridge	835.7-836.3			400	500	400
Armour	832.9-833.6			400	400	400
Grey Cloud Slough	827.3-828.0	250	400	500	500	450
Pine Bend Head Light	825.0-826.2	200	400	350	400	400
Pine Bend Foot Light	823.3-824.3	250	375	350	375	375
Grey Cloud Landing	822.3-823.3	250	400	400	400	400
Boulanger Bend	820.3-821.5	250	450	500	500	500
Boulanger Bend Lower Light	818.4-820.3	250	450	450	500	400
Nininger, Minnesota	817.8-818.4	250	400	400	500	400
Upper Approach - Lock and Dam 2	815.6-816.9			500	600	500
Hastings Highway Bridge	813.8-814.2			450	450	450
Point Douglas, Wisconsin	812.4-813.0	250	400	400	500	400
Prescott, Wisconsin	810.0-810.7	300	450	500	600	450
Truedale Slough	808.2-808.8	200	350	350	400	400
Four Mile Island	807.2-807.8	350	450	500	500	500
Below Wind Creek	800.8-800.7	300	500	500	500	450
Below Diamond Bluff	798.7-799.5	250	400	400	500	400
Upper Approach - Lock and Dam 3	797.0-798.4	300	600	600	700	600
Trenton, Wisconsin	794.0-794.5	200	600	600	650	600
Above Red Wing Highway Bridge	790.5-792.0	300	500	350-450	400-600	500
Below Red Wing Highway Bridge	789.4-790.3	200	500	500	600	500
Goose Bay	787.5-788.6	200	350	350	400	350
Head of Lake Pepin	785.2-785.6	300	450	450	550	500
Reads Landing	762.4-763.3	100	450	500	600	500
Below Reads Landing	761.5-762.5	300	450	550	600	500
Crats Island	758.0-759.5	100	500	450	600	450
Above Teepeeota Point	757.2-757.8	350	500	500	550	500
Beef Slough	753.7-754.6	200	400	400	450	400
Alma Lower Light	751.0-752.1			450	450	450
Upper Mouth - Zumbro River	749.4-751.0			500	550	500
Mule Bend	747.8-748.8	200	450	500	600	500
West Newton	747.0-747.8	250	450	400	600	450
Below West Newton	746.4-746.9	300	500	450	650	450
Lower Zumbro	744.9-745.4	350	500	500	650	500
Summerfield Island	742.8-743.6	150	400	400	500	400
Minneiska, Minnesota	742.0-743.0			500	600	500
Mount Vernon Light	740.3-741.3	200	500	500	500	500
Richtman Light	739.3-740.3			550	600	550
Upper Approach - Lock and Dam 5	738.1-739.0			500	500	500
Island 58	734.0-735.0	200	500	500	600	500
Fountain City	732.7-733.5	250	400	400	500	400
Head of Betsy Slough	731.7-732.3	250	500	500	600	500
Betsy Slough Bend	731.0-731.7	250	450	450	500	500
Wilds Bend	729.5-731.0	250	450	500	500	450
Island 71	726.0-726.7	300	450	450	500	450
Gravel Point	721.6-722.4	300	500	600	600	500
Blacksmith Slough	718.0-719.0			550	700	550
Lamoille, Minnesota	715.6-716.6			500	600	500
Head of Richmond Island	712.6-713.4	250	450	400	600	450
Queens Bluff	711.0-712.0	200	500	500	600	500
Winters Landing	708.0-709.0	200	500	300	600	400
Dakota, Minnesota	706.0-707.4	150	400	400	500	400
Black River	698.0-698.7			600	600	600
Broken Arrow	695.8-696.8	300	500	450	600	450

ST. PAUL DISTRICT RECOMMENDED BEND WIDTHS						
						April 1996
Reproduced From Attachment 3 of the GREAT I Technical Appendix E, Volume 3, September 1980						
Bend Location	River Mile	Normal Width Before Dredging	Normal Width After Dredging	Width at Last Sounding	Maximum Potential Width	Suggested Width
Sand Slough	694.4-695.2	300	600	500	700	500
Two Mile Island	691.8-692.2			500	800	500
Above Brownsville	690.2-691.0	100	400	500	650	400
Brownsville	689.7-690.2	100	500	450	600	400
Head of Raft Channel	687.5-688.4	200	400	450	500	400
Below Head of Raft Channel	686.5-687.5	250	400	350	500	400
Deadmans Slough	685.5-686.5			400	500	400
Warners Landing	683.0-683.6			400	450	400
Island 126	677.2-678.2	250	500	450	600	450
Twin Island	676.0-677.3	150	400	500	600	400
Bad Axe Bend	674.0-675.0	300	600	450	600	450
Head of Battle Island	670.7-671.5	300	450	500	500	450
Battle Island	669.8-670.7			500	600	500
Lansing Upper Light	663.8-664.4	200	600	500	800	500
Above Lansing Bridge	663.4-663.8			450	550	450
Below Lansing	660.3-661.0	300	600	450	700	450
Heytmans Crossing	654.5-655.5			500	500	500
Crooked Slough Foot Light	651.6-652.4			500	500	500
Gordons Bay	645.4-646.1	350	600	400	700	450
Mississippi Gardens	642.5-643.5	250	550	500	800	500
Johnsonport	640.6-641.8			500	600	500
Wyalusing Bend	628.6-629.3	300	600	600	700	500
Wyalusing	627.2-628.0	300	600	600	1000	500
Catfish Slough	625.7-626.6			700	800	500
Clayton, Iowa	624.7-625.7			750	900	500
French Island	619.8-620.6			500	800	500
McMillian Island	617.0-619.0	200	500	500	500	500
Ferry Slough	615.6-616.3	300	600	600	600	450
Upper Approach to Lock and Dam 10	615.1-615.6			600	600	600