

Sandbag Construction



US Army Corps of Engineers
BUILDING STRONG®



Emergency Construction Sandbags

- Typical uses:

- Where a low and relatively short barrier is required
- Constricted areas where there is no room for earthfill levees
 - ex. back yards, buildings close to channel
- Closures / temporary closures
 - ex. Roads, railroad tracks



BUILDING STRONG®

Emergency Construction Sandbags

■ Design section:

- 1:3 cross section (1 foot high for 3 foot width)
- 5 foot maximum height
- 3 foot or less height preferred



BUILDING STRONG®

Filling Sandbags

- Fill sacks approximately ½ full
- Do not tie sacks



BUILDING STRONG®


Placement of Sandbags

- Start upstream
- Where possible, strip sod / topsoil
- Where possible, excavate bonding trench 1 sack deep by 2 sacks wide
- Alternate direction of placement of bags with bottom layer parallel to flow
- Lap unfilled portion of sandbag under new sack



BUILDING STRONG®

Placement of Sandbags (cont.)




Overlap unfilled portion of sack with filled portion of next sack




BUILDING STRONG®

Placement of Sandbags (cont.)



BUILDING STRONG®

Placement of Sandbags (cont.)



Place poly on wet side of sandbag closure to prevent / reduce seepage



BUILDING STRONG®

Placement of Sandbags (cont.)

- Number of sandbags required per foot of closure vs. sandbag closure height

Height in Feet

1

2

3

4

5

Bags Required

5

10

21

36

55



BUILDING STRONG®



Sandbag placement exercise



BUILDING STRONG®



Sandbag ring levee with poly on inside face to prevent seepage



BUILDING STRONG®



Sandbag ring levee to contain seepage



BUILDING STRONG®



Sandbags placed at apartment building



BUILDING STRONG®

Seepage/Erosion Protection: Polyethylene Sheeting and Sandbags



BUILDING STRONG®


Seepage/Erosion Protection: Polyethylene Sheeting and Sandbags

- Polyethylene (poly) Sheeting - ~6 mil thick
- Sandbags used to anchor poly in place
- Placement is fairly quick
- Materials inexpensive
- Place materials in the dry or in the wet



BUILDING STRONG®

Seepage/Erosion Protection: Poly Sheeting and Sandbags (cont)




Placement of poly sheeting and sandbags in the dry



BUILDING STRONG®

Seepage/Erosion Protection: Poly Sheeting and Sandbags (cont)




Placement of poly sheeting and sandbags in the dry



BUILDING STRONG®

Seepage/Erosion Protection: Poly Sheeting and Sandbags (cont)



Placement of poly sheeting and sandbags in the wet



BUILDING STRONG®



Placement of poly on riverward side of levee to prevent seepage / erosion. Poly weighted down with sandbags



BUILDING STRONG®



Placement of poly on riverside of levee to prevent erosion / seepage



BUILDING STRONG®